



K8DT-LS1CD

Monitoring relay 17.5 mm wide, Conductive level control for liquid, 10k to 100k Ohm, 1 x SPDT, 24 V AC/DC

Application	Ordinary purified water, Sewage water
Functions	Conductive level control
Cable length	100 m
Installation type	DIN Rail
Terminal	Push-in
Size	17.5 mm
Supply voltage AC	20.4-26.4 V
Supply voltage DC	20.4-26.4 V
Output type	Relay
Contact description	SPDT
Body color	Black
Number of inputs for electrodes	3

Aksesuarlar



BF-1

Electrode holder, 1-pole electrode, standard type (150°C), liquid with low specific resistance



BF-3

Electrode holder, 3 way, standard type (150°C)













BF-5



BS-1

Electrode holder, 1-pol electrode, for high pressure or high temperature applications (250°C), 1.96Mpa

	F03-11	Protective cover for electrode holders PS or BF series)
	F03-12	PS Electrode Holder Mounting Plate
	F03-14 1P	Electrode separator, 1 electrode, ceramic, 250 °C max, 15 g
	F03-14 5P	Electrode separator, 5 electrodes, ceramic, 250 °C max, 30 g
	F03-60 SUS316	Set including F03-01 SUS316 electrode, F03-02 SUS316 connecting nuts, F03-03 SUS316 lock nuts
	PH-2 HAIPREN CODE 20M	Underwater Electrode, Hypalon cable, double pole, 20 m length
	PS-31 SUS304 1000MM	Electrode set, holder & electrodes, 1 m length, 4 mm diameter, non-extendable
	PS-31 SUS304 300MM	Electrode set, holder & electrodes, 0.3 m length, 4 mm diameter, non-extendable
	PS-3S	Electrode holder, 3 way
	PS-4S	Electrode holder, 4 way
	PS-5S	Electrode holder, 5 way
	Y92A-D1A	Plastic cover for H3DT & K8DT

CAD Kütüphanesi



EAC Mark removal Üretimden Kaldırılma Bildirimi

EN PDF 221 KB



K8DT-LS Conductive Level Controller Veri Sayfası

EN PDF 3,06 MB



Panel Building Broşür

TR PDF 15,9 MB